



5002 US Hwy 411 South Maryville, TN 37801
 Office: 865.856.3066 | Fax: 865.856.6833
www.GildedMirrorsInc.com

GILDED MIRRORS PRODUCT SPECIFICATIONS

Thickness		Edge Treatments				Mirror	Bevel (1c, 1d, 2)	Safety Tape (1g, 4)	Groove (1e)
mm	Inches	CC (1a)	SE (1b, 1f)	PE (1b, 1f)	HPE (1b, 1f, 3)				
~2.5	3/32"	Yes	No	No	No	Yes	No	No	No
~3.0	1/8"	Yes	Yes	Yes	No	Yes	Yes	Yes	No
~4.0	5/32"	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
~5.0	3/16"	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
~6.0	1/4"	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
~8.0	5/16"	Yes	Yes	Yes	Yes	No	Yes	No	Yes
~10.0	3/8"	Yes	Yes	Yes	Yes	No	Yes	No	Yes

CC = Clean Cut

SE = Seamed / Sanded / Swiped Edge

PE = Polished Edge (pencil-profile)

HPE = High Polished Edge (pencil-profile)

Glass substrate is available in Clear, Grey, and Bronze. The tinted glass options are limited to certain thicknesses.

Our mirrors are manufactured within our facility by applying a liquid-based silver solution (wet disposition) onto glass using a plating/galvanic process involving layers of tin/iron, silver, copper, and protective paint. All our mirrors meet ASTM C 1503. All our float glass is mirror-quality grade and meets ASTM C 1036. All products are subject to the posted Limited Product Warranty.

SPECIFICATION NOTES:

- Glass and Mirror Fabrication Maximum Sizes:
 - CC Products = 72" x 84" or 60" x 96"
 - SE / PE / HPE Products = 60" x 96"
 - Beveled Products = 48" x 72"
 - Bevel Widths = 1/4" to 2" (width availability subject to glass thickness)
 - V-Groove Products = 36" x 82"
 - Edged Pattern Cut Products = 50" x 50"
 - Safety-Tape Backing Products = 48" x 96"
- Bevels only be applied to straight edge products (i.e., not pattern cut pieces).
- HPE applied only to glass products (not mirror products).
- Safety-tape backing is available in strengths of Category 1 or 2.